



# GPG

## Diesel Generating Set

MODEL	GP-SC750 (S)
Prime Power (50Hz)	600kW/750kVA
Standby Power (50Hz)	660kW/825kVA



### Standard Features



- GPG diesel engine made by SDEC China, Model: SC33G990D2. With radiator at ambient temperature 40°C, fans are driven by belt, with safety guard, With DC 24V charge alternator.
- GPG Alternator Model: SC354F1 single bearing alternator; IP22 Protection, Insulation class H
- Stand type control panel with many kinds of Display and Protection function is equipped
- Two 12V starter maintenance free battery.
- Power output MCCB is equipped.
- Accessory: A suit of ripple flex exhaust pipe; exhaust siphon, muffler; and a set of spare parts & Tools & Documents.



- The structure is built-up, the built-in residential muffler makes the noise lower.
- Exhaust guide plate and air channel for air intake&noise reduction are mounted within soundproof canopies.
- Outside Emergency Stop Button.
- Inside power Cathode switch.
- Outside Fuel Inlet.
- Base Fuel tank is equipped, With lifting ear and forklift slots. Outside fuel inlet/return, outside lub oil and coolant drain.
- Noise level with no loads @ 7M is 77dB(A)

### Generator Ratings

Voltage (V)	Frequency (Hz)	Phases	Power Factor	Standby Current	Prime Current	Standby Power	Prime Power
			(COSφ)	(A)	(A)	(kW/kVA)	(kW/kVA)
440/254	50	3	0.8	1083.0	985.0	660/825	600/750
400/230	50	3	0.8	1191.0	1085.0	660/825	600/750
380/220	50	3	0.8	1253.0	1139.0	660/825	600/750
Other	Customizing for Different Specification						

### Sales Promises

- All the gensets are tested on load before they leave factory, various kinds of functions are tested . and test reports are provided.
- Warranty for all of our gensets and accessories is according to our standard conditions since testing: 12 months or 1,000 running hours accumulatively, subject to the earlier, kindly refer to our service terms.



# GPG

## Engine Data

Manufacturer / Model:	SDEC/SC33G990D2
Air Intake System:	4-Cycle, Turbocharger, Aftercooling
Fuel System:	Direct injection
Cylinder Arrangement:	6 cylinders Vertical in-line
Displacement:	32.8L
BorexStroke:	180x215(mm)
Compression Ratio:	15:1
Rated RPM:	1500rpm
Max. Standby Power at Rated RPM:	726kW
Governor Type:	Electronic Speed Governor

## Exhaust System

Exhaust Flow:	152.6m <sup>3</sup> /min
Exhaust Temperature:	680°C
Max Back Pressure:	8kPa

## Air Intake System

Max Intake Restriction:	6kPa
Combustion air Flow:	62.9m <sup>3</sup> /min

## Fuel System

110% Standby Power Load:	158.4L/h
100% Prime Power Load:	142.2L/h
75% Prime Power Load:	104.4L/h
50% Prime Power Load:	73.8L/h

## Oil System

Max. sump capacity	75L
--------------------	-----

## Cooling System

Total Coolant Capacity (engine only):	56L
Thermostat operation range:	77-90°C

## Electrical System

System Voltage:	DC 24 V
Rated Current for Charge Alternator:	54 A



# GPG

## Alternator Data

Manufacturer / Type:	SDEC/ SC354F1
Number of Phase:	3
Connecting Method:	3 Phase and 4 Wires, "Y" type connecting
Number of Bearing:	1
Power Factor:	0.8
Protection Grade:	IP22
Altitude Requirement:	≤1000m
Exciter Type:	Brushless, Self-exciting
Insulation Class/Temperature Rise:	H/H
Telephone Influence Factor (TIF):	<50
THF:	<2%
Voltage Regulation, Steady State :	≤±1%
Alternator Capacity:	750kVA
Alternator Efficiencies:	93.3%

## Generating Set Data

Frequency Reduce:	≤5%
Frequency Regulation, Stead State:	≤1.5%
Waveform Distortion(no load):	<1.5%
Sudden Frequency Warp (100% Sudden Reduce):	≤+12%
Sudden Frequency Warp (Sudden Increase):	≤-10%
Frequency Recovery Time (100% Sudden Reduce) :	≤5S
Frequency Recovery Time (Sudden Increase):	≤5S
Voltage Regulation:	≥±5%
Voltage Regulation, Stead State:	≤±2.5%
Voltage Modulation:	0.30%
Sudden Voltage Warp (100% Sudden Reduce):	≤+25%
Sudden Voltage Warp (100% Sudden Increase):	≤-20%
Voltage Stable Time (100% Sudden Reduce):	≤6S
Voltage Stable Time (100% Sudden Increase):	≤6S
Voltage Unbalance:	1%



# GPG

## Standard Control Panel



HKY-6110 control panel is fit for backpack structure and standing structure. This control panel is a panel which holds a HGM6110 made by Smartgen the professional module maker in China as its core intelligent control module. It has plenty friendly operation interface with many functions such as running parameter detecting, stastic, record, pre-alarm, Remote control, monitor & protection.

## Options

Engine	Alternator	Control and Power Distribution System	Others
<ul style="list-style-type: none"> <li>● 50°C High Temperature Radiator</li> <li>● Water Separator</li> <li>● Water Jacket Heater</li> <li>● Oil Heater</li> <li>● Oil Discharging Pump</li> </ul>	<ul style="list-style-type: none"> <li>● Permanent Magnet Gen-erator (PMG)</li> <li>● Anti Condensation Heater</li> <li>● Drop CT(For Paralleling)</li> </ul>	<ul style="list-style-type: none"> <li>● ComAp Control module</li> <li>● Deepsea Control module</li> <li>● Auto Transfer Switch(ATS)</li> <li>● Battery Charge</li> <li>● Manual Paralleling System</li> <li>● Auto Paralleling System</li> <li>● Electronic Indicator for Fuel Level</li> </ul>	<ul style="list-style-type: none"> <li>● Daily Fuel Tank</li> <li>● Base Fuel Tank</li> <li>● Trailer Type</li> <li>● Automatic Input System For Fuel</li> <li>● Maintenance Tools</li> <li>● Accesory Bag</li> <li>● Wind Scooper for Soundproof Canopy</li> </ul>

## Dimension & Weight

Open Type		
	Overall Size LxWxH 3500mm x 1700mm x 2000mm	
	<table border="1"> <tr> <td>Weight 7400 kg</td> <td>Base fuel tank capacity Full load running for 4~6 hours</td> </tr> </table>	Weight 7400 kg
Weight 7400 kg	Base fuel tank capacity Full load running for 4~6 hours	
Soundproof Type		
	Overall Size LxWxH 20 ft HQ Container	
	<table border="1"> <tr> <td>Weight 12000 kg</td> <td>Base fuel tank capacity Full load running for 4~6 hours</td> </tr> </table>	Weight 12000 kg
Weight 12000 kg	Base fuel tank capacity Full load running for 4~6 hours	